

FEATURES:

- UTILIZES STANDARD CAT 3, 5, OR 6 CABLE
- USED WITH TALKBACK PAGE CONTROLS
- ELECTRICALLY, ACOUSTICALLY MATCHED PARTS



DESCRIPTION:

Wall surface mounted speaker assembly complete with 45-ohm speaker, sloped baffle and mounting bracket.

Specifications:

SPEAKER ELEMENT

Cone Diameter: 8.0" (20.32 cm)
Voice Coil Impedance: 45 ohm

FREQUENCY RESPONSE

80 Hz to 15 kHz

SPEAKER POWER RATING

12 Watts

HOUSING AND FINISH

Baffle constructed of .5" (1.27 cm) particle board, covered with simulated walnut vinyl with brown grille cloth.

ENVIRONMENT

Temperature: -4 to +131°F (-20 to +55 °C)
Humidity: 0-95% Non-Condensing

DIMENSIONS AND WEIGHT

9.6 "H x 11.5 "W x 4.2 "D (24.38 cm x 29.21 cm x 10.67 cm)
Weight: 4.0 lbs (1.8 kg)
Shipping Weight: 4.5 lbs (2.05 kg)

ARCHITECTS' AND ENGINEERS

The Wall Speaker, Model V-1063A shall consist of a 45-ohm speaker and sloped baffle. The speaker, housing and hardware shall be electrically and acoustically matched for a frequency response of 80 Hz to 15 kHz. The speaker element shall be cone type with 5 oz (142 g) ceramic magnet. Diameter of speaker cone shall be 8.0" (20.32 cm) with 2.0" (5.08 cm) whizzer cone. Voice coil diameter shall be .75" (1.91 cm). Voice coil impedance shall be 45-ohm. Speakers utilizing an 8-ohm voice coil are not acceptable. Operating temperature shall be -4 to + 131 °F (-20 to + 55 °C).

The baffle shall be constructed of .5" (1.27 cm) particle board covered with simulated walnut vinyl with brown grille cloth.

Maximum dimensions of the housing shall be 9.6 "H x 11.5 "W x 4.2 "D (24.38 cm x 29.21 cm x 10.67 cm). Approximate weight is 4.0 lbs (1.8 kg).

LIMITED WARRANTY

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened (A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor)

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event, shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.