

FEATURES:

- LOOP START TRUNK PORT AND PAGE PORT ACCESS
- ONE WAY PAGE
- INTEGRATED POWER SUPPLY
- BACKGROUND MUSIC INPUT
- VOICE OPERATED MUSIC MUTE
- PROVIDES EXTERNAL POWER FOR ONE-WAY AMPLIFIED SPEAKERS
- WALL OR SHELF MOUNT



DESCRIPTION:

A telephone-compatible one-zone, one-way page control unit with integrated power supply, and background music input.

Specifications:

INPUTS/OUTPUTS

Input Impedance: 600 ohms
Music Source Impedance: 8 to 600 ohms
Music Input Level: -10 dBm nominal
Voice Switch Sensitivity: -21 dBm
Output Impedance: 8 ohms
Output Level: -10 dBm nominal
DC Output: -24 Vdc @ 600 mA

CONTROLS

Page Volume
 Background Music Volume

CONNECTIONS:

Screw terminals are provided for all connections.
 An RJ11 jack is provided for tip and ring input connection.

POWER REQUIREMENT

.35 Amp at 120 Vac

ENVIRONMENT

Temperature: +32 to +104 °F (0 to +40 °C)
 Humidity: 0-85% Non-Condensing

HOUSING AND FINISH

Gray painted aluminum alloy

DIMENSIONS AND WEIGHT

2.6 "H x 7.7 "W x 5.3 "D (6.604 cm x 19.558 cm x 13.462 cm).
 Weight: 2.6 lbs (1.17 kg)
 Shipping Weight: 3.5 lbs (1.575 kg)

ARCHITECTS' AND ENGINEERS

The One-Zone Basic Integrated Page Control, Model V-2000A shall be a wall or shelf mounted, telephone compatible, one-zone, one-way, page control unit with integrated power supply. The unit shall provide a page input, and background music input. The unit shall provide voice activated switching to automatically cut off music during a voice page. Volume controls shall be provided to control page and background music levels.

In connection with a telephone system, the unit shall have the ability to provide loop current to the system for access. In connection with a telephone system page port, a "dry" tip and ring connection shall be provided. A battery feed switch located on the unit shall turn loop current on or off to the tip and ring connections.

The unit shall provide both screw terminals and an RJ11 jack for page tip and ring input connections. Screw terminals shall be provided for music input and all output connections.

The unit shall provide a three-conductor grounded power cord with NEMA 15-5P type plug for AC input and shall provide auxiliary -24 Vdc and GND outputs. The outputs shall provide 600 mA @ -24 Vdc for powering one-way amplified speakers or other accessory devices. The chassis shall be AC grounded. The AC input shall be fuse protected at .5 Amp.

The unit shall be UL Listed.

The unit shall have a power consumption of .35 Amp @ 120 Vac. Both page inputs shall have an impedance of 600 Ohms. Music source impedance shall be 8 to 600 ohms. Music input level shall be -10 dBm nominal. Voice switch sensitivity shall be -21 dBm. Output impedance shall be 8 ohms. Output level shall be -10 dBm nominal. Operating temperature shall be +32 to 104 °F (0 to + 40 °C). Operating humidity level shall be 0% to 85% non-condensing. The housing of the unit shall be constructed of gray painted aluminum alloy. The maximum dimensions shall be 2.6 "H x 7.7 "W x 5.3 "D (6.604 cm x 19.558 cm x 13.462 cm). Weight shall be approximately 2.6 lbs (1.17 kg).

LIMITED WARRANTY

Valcom, Inc. warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the re-placement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Valcom, Inc. indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened (A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Valcom, Inc. are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (major repairs will be subject to additional charges for parts and labor)

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event, shall Valcom, Inc. be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.